## 11G48560



DELAYED AUXILIARY CONTACT 1NO+1NC (PNEUMATIC OPERATION) ON ENERGISATION FOR FRONT CENTRE MOUNTING. SCREW TERMINALS, FOR BF... SERIES CONTACTORS, 60S



Mechanical features	
Fixing	Front centre
Auxiliary contact characteristics	mounting
Type of contact	1NO + 1NC
Dimensions	
(1.10") (1.10") (1.80") (1.80") (1.80") (1.9L") (1.	
Wiring diagrams	
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	
Certifications and compliance	
Compliance	
CSA C22.2 p <sup>6</sup> 60047.1	

	CSA C22.2 n° 60947-1				
	CSA C22.2 n° 60947-5-1				
	IEC/EN 60947-1				
	IEC/EN 60947-5-1				
	UL 60947-1				
	UL 60947-5-1				
Certificates					
	CCC				

11G48560



DELAYED AUXILIARY CONTACT 1NO+1NC (PNEUMATIC OPERATION) ON ENERGISATION FOR FRONT CENTRE MOUNTING. SCREW TERMINALS, FOR BF... SERIES CONTACTORS, 60S

CSA			
cURus			
EAC			

ETIM classification

**ETIM 8.0** 

EC002498 -Accessories/spare parts for lowvoltage switch technology