

DELAYED AUXILIARY CONTACT 1NO+1NC (PNEUMATIC OPERATION) ON DE-ENERGISATION FOR FRONT CENTRE MOUNTING. SCREW TERMINALS, FOR BF... SERIES CONTACTORS, 15S



11G48615

Mechanical features	
Fixing	Front centre
	mounting
Auxiliary contact characteristics Type of contact	1NO + 1NC
Dimensions	
28	
(1.10")	
	7
	44.7 1.76")
	1.7
	1
	_
Wiring diagrams	
67 55	
$\gamma \gamma = 7$	
-)/	
68 56	
Certifications and compliance	
Compliance	
CSA C22.2 n° 60947-1	
CSA C22.2 n° 60947-5-1 IEC/EN 60947-1	
IEC/EN 60947-5-1	
UL 60947-1	
UL 60947-5-1	
Certificates	
CCC	



DELAYED AUXILIARY CONTACT 1NO+1NC (PNEUMATIC OPERATION) ON DE-ENERGISATION FOR FRONT CENTRE MOUNTING. SCREW TERMINALS, FOR BF... SERIES CONTACTORS, 15S

CSA			
cURus			
EAC			

ETIM classification

ETIM 8.0

EC002498 -Accessories/spare parts for lowvoltage switch technology