

11G487 DELAYED AUXILIARY CONTACT 1NO+1NC (PNEUMATIC OPERATION) ON DE-ENERGISATION FOR FRONT CENTRE MOUNTING. SCREW TERMINALS, FOR BF... SERIES CONTACTORS, 70MS



Mechanical features	
Fixing	Front centre
Auxiliary contact characteristics	mounting
Type of contact	1NO + 1NC
Dimensions	
28	
(1.10")	
	76")
	1.7
Wiring diagrams	
67 55	
$\gamma\gamma$ \neq	
-)- < /	
68 56	
Certifications and compliance	
Compliance	
CSA C22.2 n° 60947-1	
CSA C22.2 n° 60947-5-1	
IEC/EN 60947-1	
IEC/EN 60947-5-1	
UL 60947-1 UL 60947-5-1	
Certificates	
Oertificates	

CCC



DELAYED AUXILIARY CONTACT 1NO+1NC (PNEUMATIC OPERATION) ON DE-ENERGISATION FOR FRONT CENTRE MOUNTING. SCREW TERMINALS, FOR BF... SERIES CONTACTORS, 70MS

CSA			
cURus			
EAC			

ETIM classification

ETIM 8.0

EC002498 -Accessories/spare parts for lowvoltage switch technology