
ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 > 0 < 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 0



| Product designation | | | | Selector switch actuator key - 3 position |
|-------------------------|-----------------------|-----|--------|---|
| Product type designati | | | | LPFS37 |
| General characteristics | S | | | |
| Colour | | | | Black |
| Type of positions | | | | 1 > 0 < 2, key extraction in 0 |
| Material | | | | Aluminium and zinc alloy |
| IEC degree of protect | ion | | | IP66, IP67 and IP69K |
| Mechanical features | | | | |
| Mechanical life | | | cycles | 1000000 |
| Fixing | | | | Without mounting adapter |
| Mounting adapter | | | | LPXAU120M |
| UL technical data | | | | |
| UL degree of protection | | | | Type1, 2, 3R, 4, 4X, 12, 12K |
| Ambient conditions | | | | |
| Temperature | | | | |
| | Operating temperature | | | |
| | | min | °C | -25 |
| | | max | °C | +70 |
| | Storage temperature | | | |
| | | min | °C | -40 |
| | | max | °C | +85 |
| Dimensions | | | | |



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 **UL508**

Certificates

cULus

ETIM classification





SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 > 0 < 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 0

ETIM 8.0

EC002611 -Control switch