
ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 > 0 - 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 2



Product type designation General characteristics Colour Type of positions Material IEC degree of protection Mechanical features Mechanical life Cycles 1000000 Without mounting
ColourBlackType of positions1 > 0 - 2, key extraction in 2MaterialAluminium and zinc alloyIEC degree of protectionIP66, IP67 and IP69KMechanical featurescycles1000000
Type of positions Material Material IEC degree of protection Mechanical features Mechanical life 1 > 0 - 2, key extraction in 2 Aluminium and zinc alloy IP66, IP67 and IP69K Mechanical features Cycles 1000000
Material zinc alloy IEC degree of protection IP66, IP67 and IP69K Mechanical features Mechanical life cycles 1000000
Mechanical features Mechanical life cycles 1000000
Mechanical life cycles 1000000
- <u></u>
Without mounti
Fixing adapter
Mounting adapter LPXAU120M
UL technical data
UL degree of protection Type1, 2, 3R, 4 4X, 12, 12K
Ambient conditions
Temperature
Operating temperature
min °C -25
max °C +70
Storage temperature
min °C -40
max °C +85

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-5-1

UL508

Certificates

cULus

ETIM classification



ENERGY AND AUTOMATION

LPFS380R621E

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 > 0 - 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 2

ETIM 8.0

EC002611 -Control switch