


LPFS390R421E SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 < 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 1



Product designation Product type designation				Selector switch actuator key - 3 position LPFS39
General characteristics				ELLOSS
Colour				Black
Type of positions				1 - 0 < 2, key extraction in 1
Material				Aluminium and zinc alloy
IEC degree of protection				IP66, IP67 and IP69K
Mechanical features				
Mechanical life			cycles	1000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
Ope	erating temperature			
		min	°C	-25
		max	°C	+70
Sto	rage temperature			
		min	°C	-40
Dimensions		max	°C	+85



Key Certifications and compliance Compliance CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508 Certificates cULus ETIM classification

LPFS390R421E



ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 < 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 1

ETIM 8.0

EC002611 -Control switch