
SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 < 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 1



Product designation Product type designation			Selector switch actuator key - 3 position LPFS39
General characteristics			2. 1 000
Colour			Black
Type of positions			1 - 0 < 2, key extraction in 1
Material			Aluminium and zinc alloy
IEC degree of protection			IP66, IP67 and IP69K
Mechanical features			
Mechanical life		cycles	1000000
Fixing			Without mounting adapter
Mounting adapter			LPXAU120M
UL technical data			
UL degree of protection			Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions			
Temperature			
Operating temperature			
	min	°C	-25
	max	°C	+70
Storage temperature			
	min	°C	-40
Dimensions	max	°C	+85



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 **UL508**

Certificates

cULus

ETIM classification





SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1-0 < 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 1

ETIM 8.0

EC002611 -Control switch