


LPFS390R621E SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 < 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 1



General characteristics Colour Black Type of positions 1 - 0 < 2, key extraction in 1 Material Aluminium and zinc alloy IEC degree of protection IP66, IP67 and IP69K Mechanical features IP66, IP67 and IP69K Mechanical life cycles Munting adapter LPXAU120M UL technical data Type1, 2, 3R, 4, 4X, 12, 12K Ambient conditions Type1, 2, 3R, 4, 4X, 12, 12K Temperature min °C Operating temperature min °C Storage temperature min °C max °C +85	Product designation Product type designat	tion			Selector switch actuator key - 3 position LPFS39
Type of positions 1 - 0 < 2, key extraction in 1 Material Aluminium and zinc alloy IEC degree of protection IP66, IP67 and IP69K Mechanical features IP69K Mechanical life cycles 100000 Fixing Without mounting adapter Without mounting adapter Mounting adapter LPXAU120M UL technical data UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K Type1, 2, 3R, 4, 4X, 12, 12K Ambient conditions T Type1, 2, 3R, 4, 4X, 12, 12K Image temperature min °C -25 max °C +70 -25 max °C +70 Storage temperature min °C -40 -40					
Type of positions extraction in 1 Material Aluminium and zinc alloy IEC degree of protection IP66, IP67 and IP69K Mechanical features IP69K Mechanical features Without mounting adapter Mounting adapter LPXAU120M UL technical data Type1, 2, 3R, 4, 4X, 12, 12K Ambient conditions Type1, 2, 3R, 4, 4X, 12, 12K Temperature Operating temperature Min °C Storage temperature min min °C Mounting temperature min Min °C Mounting temperature min Min °C Min °C Multiplication 100000 Multiplication 100000 Multiplication 100000 Multiplication 100000 Multiplication 100000	Colour				Black
Material zinc alloy IEC degree of protection IP66, IP67 and IP69K Mechanical features Without mounting adapter Mechanical life cycles 100000 Without mounting adapter Mounting adapter LPXAU120M UL technical data UL degree of protection UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K Ambient conditions Temperature Operating temperature min °C +70 Storage temperature min °C min °C -40	Type of positions				•
Mechanical features IP69K Mechanical life cycles 100000 Fixing Without mounting adapter Without mounting adapter Mounting adapter LPXAU120M UL technical data Type1, 2, 3R, 4, 4X, 12, 12K UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K Ambient conditions Toperating temperature Vertical data Vertical data Mounting adapter Type1, 2, 3R, 4, 4X, 12, 12K	Material				
Mechanical life cycles 100000 Fixing Without mounting adapter without mounting adapter Mounting adapter LPXAU120M UL technical data Type1, 2, 3R, 4, 4X, 12, 12K UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K Ambient conditions Temperature Operating temperature min °C -25 max °C +70 Storage temperature min °C -40	IEC degree of protection				
Fixing Without mounting adapter Mounting adapter LPXAU120M UL technical data Type1, 2, 3R, 4, 4X, 12, 12K UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K Ambient conditions Temperature Operating temperature min °C -25 max °C +70 Storage temperature min °C -40	Mechanical features				
Fixing adapter Mounting adapter LPXAU120M UL technical data Type1, 2, 3R, 4, 4X, 12, 12K UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K Ambient conditions Temperature Operating temperature min °C -25 max °C +70 Storage temperature min °C -40	Mechanical life			cycles	1000000
UL technical data Type1, 2, 3R, 4, 4X, 12, 12K UL degree of protection Type1, 2, 3R, 4, 4X, 12, 12K Ambient conditions Temperature Temperature 0perating temperature Min °C -25 max Storage temperature min °C +70 Storage temperature min °C -40	Fixing				
UL degree of protection Type1, 2, 3R, 4, Ambient conditions Temperature Operating temperature $ \begin{array}{ccccccccccccccccccccccccccccccccccc$	Mounting adapter				LPXAU120M
Ambient conditions 4X, 12, 12K Ambient conditions 7 Temperature 0perating temperature	UL technical data				
Temperature Operating temperature min °C -25 max °C +70 Storage temperature min °C -40	UL degree of protection	on			
Operating temperature min °C -25 max °C +70 Storage temperature min °C -40	Ambient conditions				
min °C -25 max °C +70 Storage temperature min °C -40	Temperature				
max °C +70 Storage temperature min °C -40		Operating temperature			
Storage temperature min °C -40			min	°C	-25
min °C -40			max	°C	+70
		Storage temperature			
max °C +85			min	-	-
Dimensions			max	°C	+85



Key Certifications and compliance Compliance CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508 Certificates cULus ETIM classification

LPFS390R621E



ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø30MM PLATINUM SERIES FLAT METAL, 3 POSITION, 1 - 0 < 2 WITH DIFFERENT KEY CODE. WITHDRAL AT 1

ETIM 8.0

EC002611 -Control switch