


PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES METAL, FLUSH, STOP/BLACK



| Product designation | | | | | Pushbutton actuators, spring return, with symbol |
|--------------------------|-----------------------|--|-----|--------|---|
| Product type designation | | | | | LPSB11 |
| General characteristics | 3 | | | | |
| Colour | | | | | Black |
| Type of positions | | | | | Flush pushbutton |
| Material | | | | | Aluminium and zinc alloy |
| IEC degree of protection | | | | | IP66, IP67 and IP69K |
| Mechanical features | | | | | |
| Operating force | | | | kg-lb | <0.5Kg / 1.1lb |
| Mechanical life | | | | cycles | 5000000 |
| Fixing | | | | | Without mounting adapter |
| Mounting adapter | | | | | LPXAU120M |
| UL technical data | | | | | |
| UL degree of protection | | | | | Type1, 2, 3R, 4, 4X, 12, 12K |
| Ambient conditions | | | | | |
| Temperature | | | | | |
| | Operating temperature | | | | |
| | | | min | °C | -25 |
| | | | max | °C | +70 |
| | Storage temperature | | | | |
| | | | min | °C | -40 |
| | | | max | °C | +85 |
| Dimensions | | | | | |

10



Certifications and compliance

Compliance

CSA C22.2 n° 14 IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1 UL508

Certificates

cULus

ETIM classification



ENERGY AND AUTOMATION

LPSB1132

PUSHBUTTON ACTUATOR, SPRING RETURN, WITH SYMBOL Ø22MM PLATINUM SERIES METAL, FLUSH, STOP/BLACK

ETIM 8.0

EC000221 -Front element for push button