
ENERGY AND AUTOMATION

SELECTOR SWITCH ACTUATOR KEY Ø22MM PLATINUM SERIES METAL, 3 POSITION, 1 > 0 -2 WITH DIFFERENT KEY CODE. WITHDRAL AT 0



				Selector switch
Product designation				actuator key - 3 position
Product type designati	on			LPSS35
General characteristics				
Colour				Black
Type of positions				1 > 0 - 2, key extraction in 0
Material				Aluminium and zinc alloy
IEC degree of protecti	on			IP66, IP67 and IP69K
Mechanical features				
Mechanical life			cycles	1000000
Fixing				Without mounting adapter
Mounting adapter				LPXAU120M
UL technical data				
UL degree of protection				Type1, 2, 3R, 4, 4X, 12, 12K
Ambient conditions				
Temperature				
	Operating temperature			
		min	°C	-25
	<u> </u>	max	°C	+70
	Storage temperature		°C	40
		min max	°C	-40 +85
Dimensions		IIIdx	J	. 55



Certifications and compliance

Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1 IEC/EN/BS 60947-5-1

UL508

Certificates

cULus

ETIM classification

ETIM 8.0

EC002611 -Control switch