



Product designation				Rotary cam switches		
Product type designation				7GN63		
<b>General characteristics</b>						
Switching diagram				109 - Multi-step 0-1-2-3-4 1 pole		
N° of elements				2		
Mounting form				U - Front mounting with black handle		
<b>Contact characteristics</b>						
Rated insulation voltage $U_i$	IEC/EN	V	690			
	UL/CSA	V	600			
Rated impulse withstand voltage $U_{imp}$			kV	6		
Conventional free air thermal current $I_{th}$	IEC/EN	A	63			
	UL/CSA	A	60			
Rated operational voltage			V	480		
Rated operational impulse voltage			kV	4		
Maximum fuse size for short-circuit protection $I_n$ (gG)	10kA	A	63			
	15kA	A	63			
	25kA	A	63			
	50kA	A	63			
	63kA	A	63			
Rated short time current $I_{cw}$	1s	kA	1600			
				10/5 mA/V		
Conductivity				10/5 mA/V		
Operational current $I_e$ IEC/EN	AC1/AC21A			A	63	
	AC15			110V	A	32
Rated operational power in AC				220/230V	A	25
				380/400V	A	15
				660/690V	A	4
	Three-phase AC-3			220/230V	kW	11
				380/440V	kW	18.5
				500/690V	kW	18.5
	Single-phase AC-3			110V	kW	3.7
				220/230V	kW	6.5
				380/440V	kW	11.5
	Three-phase AC23A			220/230V	kW	12.5
			380/440V	kW	30	
			500/690V	kW	30	
Single-phase AC23A			110V	kW	3.7	
			220/230V	kW	7.5	

	380/440V	kW	12.5
Rated operational current in DC			
DC21A	48V	A	63
	60V	A	50
	110V	A	8
	220V	A	1
DC23A (poles in series)	24V	A	50 (1)
	48V	A	50 (2)
	60V	A	50 (3)
	110V	A	25 (3)
	220V	A	15 (4)
DC13	24V	A	63
	48V	A	40
	60V	A	28
	110V	A	3.3
Power dissipation		W	3.4
<b>Mechanical features</b>			
Terminals screw			M5
Tightening torque for terminals max		Nm	2
Conductor size			
AWG - Rigid cable	min	AWG	14
	Max	AWG	6
AWG - Flexible cable	min	AWG	14
	Max	AWG	8
Conductor size (IEC) - Flexible cable	min	mm <sup>2</sup>	2.5
	Max	mm <sup>2</sup>	10
Conductor size (IEC) - Rigid cable	min	mm <sup>2</sup>	2.5
	Max	mm <sup>2</sup>	16
Mechanical life		cycles	5x10 <sup>6</sup>
<b>UL technical data</b>			
Motor power for direct-on-line control			
for three-phase motor	120V	HP	7.5
	240V	HP	15
	480V	HP	25
	600V	HP	25
for single-phase motor	120V	HP	3
	240V	HP	10
<b>Ambient conditions</b>			
Temperature			
Operating temperature	min	°C	-25
	max	°C	+55
Storage temperature	min	°C	-40
	max	°C	+70

**Resistance & Protection**

Frontal IP degree	IP40
Terminals IP degree	IP00


**Dimensions**



Standard drillings for 7GN125.  
Drillings on request for 4 screws fixing  
(4V version).

Series	Dimensions									L Number of elements											
	□A	C	ØD	ØD1	ØD2	E	ØG	□K	□N	1	2	3	4	5	6	7	8	9	10	11	12
7GN12	48	39.5	39	12	5	26.5	38	36	6	36.1	45.8	55.5	65.2	74.9	84.6	94.3	104	113.7	123.4	133.1	142.8
7GN20	48	39.5	39	12	5	26.5	38	36	6	36.1	45.8	55.5	65.2	74.9	84.6	94.3	104	113.7	123.4	133.1	142.8
7GN25	48	39.5	43	12	5	26.5	38	36	6	40.5	54.1	67.7	81.3	94.9	108.5	122.1	135.7	147.3	162.9	176.5	190.1
7GN32	65	53	58	14	5	34.5	58.5	48	7	46.5	61.6	76.7	91.8	106.9	122	137.1	152.2	167.3	182.4	197.5	212.6
7GN40	65	53	58	14	5	34.5	58.5	48	7	46.5	61.6	76.7	91.8	106.9	122	137.1	152.2	167.3	182.4	197.5	212.6
7GN63	65	53	62	14	5	34.5	58.5	48	7	50.3	68.4	86.5	104.6	122.7	140.8	158.9	177	195.1	213.2	231.3	249.4
7GN125	90	70.5	86	16	6	41.5	84	68	9	67.3	96.4	125.5	154.6	183.7	220.3	249.4	278.5	307.6	336.7	365.8	394.9

**Wiring diagrams**



0				
1	X			
2			X	
3		X		
4				X

109

**Certifications and compliance**

**Compliance**

- CSA C22.2 n° 14
- IEC/EN/BS 60947-1
- IEC/EN/BS 60947-3
- IEC/EN/BS 60947-5-1
- UL60947-4-1

**Certificates**

- cCSAus
- EAC
- UL

**ETIM classification**

ETIM 8.0

EC001029 -  
Selector switch,  
complete