

| | | | |
|---|--|----|-----------|
| Product designation | Rotary cam switches | | |
| Product type designation | GX32 | | |
| General characteristics | | | |
| Switching diagram | 53 - Changeover switch 3 poles - 2 speed motor starting with separate windings | | |
| N° of elements | 3 | | |
| Mounting form | U25 - Front mounting with red/yellow handle padlockable in 0 and protection covers | | |
| Contact characteristics | | | |
| Rated insulation voltage U_i | IEC/EN | V | 690 |
| | UL/CSA | V | 600 |
| Rated impulse withstand voltage U_{imp} | | kV | 6 |
| Conventional free air thermal current I_{th} | IEC/EN | A | 32 |
| | UL/CSA | A | 32 |
| Rated operational voltage | | V | 440 |
| Rated operational impulse voltage | | kV | 4 |
| Maximum fuse size for short-circuit protection I_n (gG) | 10kA | A | 35 |
| | 15kA | A | 35 |
| | 25kA | A | 35 |
| Rated short time current I_{cw} | 1s | kA | 1000 |
| Conductivity | | | 10/5 mA/V |
| Operational current I_e IEC/EN | | | |
| AC1/AC21A | | A | 32 |
| AC15 | 110V | A | 25 |
| | 220/230V | A | 20 |
| | 380/400V | A | 10 |
| | 660/690V | A | 2 |
| Rated operational power in AC | | | |
| Three-phase AC-3 | 220/230V | kW | 7.5 |
| | 380/440V | kW | 11 |
| | 500/690V | kW | 11 |
| Single-phase AC-3 | 110V | kW | 1.8 |
| | 220/230V | kW | 3.5 |
| | 380/440V | kW | 5.5 |
| Three-phase AC23A | 220/230V | kW | 8 |
| | 380/440V | kW | 15 |

| | | | |
|--|----------|-----------------|-------------------|
| | 500/690V | kW | 15 |
| Single-phase AC23A | | | |
| | 110V | kW | 2.2 |
| | 220/230V | kW | 3.5 |
| | 380/440V | kW | 6 |
| Rated operational current in DC | | | |
| DC21A | | | |
| | 48V | A | 32 |
| | 60V | A | 32 |
| | 110V | A | 5 |
| | 220V | A | 0.8 |
| | 440V | A | 0.25 |
| DC23A (poles in series) | | | |
| | 24V | A | 32 (1) |
| | 48V | A | 32 (2) |
| | 60V | A | 32 (3) |
| | 110V | A | 15 (3) |
| | 220V | A | 12 (4) |
| DC13 | | | |
| | 24V | A | 32 |
| | 48V | A | 25 |
| | 60V | A | 14 |
| | 110V | A | 3 |
| | 220V | A | 0.5 |
| | 440V | A | 0.15 |
| Power dissipation | | W | 1.6 |
| Mechanical features | | | |
| Terminals screw | | | M4 |
| Tightening torque for terminals max | | Nm | 1.2 |
| Conductor size | | | |
| AWG - Rigid cable | | | |
| | min | AWG | 16 |
| | Max | AWG | 8 |
| AWG - Flexible cable | | | |
| | min | AWG | 16 |
| | Max | AWG | 10 |
| Conductor size (IEC) - Flexible cable | | | |
| | min | mm ² | 1.5 |
| | Max | mm ² | 6 |
| Conductor size (IEC) - Rigid cable | | | |
| | min | mm ² | 1.5 |
| | Max | mm ² | 10 |
| Mechanical life | | cycles | 1X10 ⁶ |
| UL technical data | | | |
| Motor power for direct-on-line control | | | |
| for three-phase motor | | | |
| | 120V | HP | 3 |
| | 240V | HP | 7.5 |
| | 480V | HP | 15 |
| | 600V | HP | 15 |
| for single-phase motor | | | |
| | 120V | HP | 1.5 |
| | 240V | HP | 3 |
| Ambient conditions | | | |

Temperature

Operating temperature

| | | |
|-----|----|-----|
| min | °C | -25 |
| max | °C | +55 |

Storage temperature

| | | |
|-----|----|-----|
| min | °C | -40 |
| max | °C | +70 |

Resistance & Protection

| | |
|-------------------|------|
| Frontal IP degree | IP65 |
|-------------------|------|

| | |
|---------------------|------|
| Terminals IP degree | IP20 |
|---------------------|------|

ETIM classification

ETIM 8.0

EC001029 -
 Selector switch,
 complete